

FARMALL A



SPECIFICATIONS**FARMALL A 125
CAB & ROPS****FARMALL A 140
ROPS ONLY****POWER**

Type	Tier 3	Tier 3
Engine HP at 2,200 RPM	125	140
PTO HP at 1,900 RPM	105	115
Cylinders / Displacement	6 cyl. / 6.7 L (411 cu in.)	
Number of Valves	12	
Aspiration	Turbocharged	

ELECTRICAL

Alternator Standard	120 Amp
Battery Standard	12V-950 CCA

TRANSMISSION / PTO

Standard (Base)	8F × 8R with Power Shuttle
Optional	8F × 8R with Synchronized Mechanical Reverser
Optional	16F × 8R with Power Shuttle and Hi-Lo
PTO - Standard / Optional Independent	540 / 1000 RPM with Two Individual Shafts

AXLES

Standard / Rear Axle	Flange / Bar	
Bar Axle Diameter	3.1 in. (78 mm)	
Rear Bar Axle Length	98 in. (2 489 mm)	
Front Axle - Standard / Optional	2WD / Class 3 Non-Suspended Standard-Duty	
Tread Adjustability	64.0 in. – 80.0 in. (1 626 – 2 032 mm)	
Wheelbase Standard 2WD / MFD	101 in. (2 471 mm) /	105 in. (2 667 mm) /
	99 in. (2 520 mm)	104 in. (2 642 mm)
Rear Axle Ratio	31.714	
Rear Tire Size	18.4-34 R1	
Rolling Radius in/mm	31.3 / 795.0	

HYDRAULICS / HITCH

System Type Standard	Fixed Displacement Pump (FD)
Remotes - Standard / Optional	2 Deluxe Remotes / 4 Deluxe Remotes
Implement Flow Capacity	22 gpm (83 ℓ/min)
Steering / Secondary Pump Capacity	9 gpm (34 ℓ/min)
Standard Tractor Hydraulic Total Flow Capacity	31 gpm (117 ℓ/min)
3-Point Hitch Category	Cat II standard
Hitch Lift Capacity at 24 in. Standard w/2 External Cylinders	7,200 lbs. (3 266 kg)

CAPACITIES

Fuel Tank 40 gal. (150 ℓ) 62 gal. (235 ℓ)
Engine Oil with Filter 11.6 qt. (11 ℓ) 14.8 qt. (14 ℓ)
Hydraulic Fluid 65.5 qt. (62 ℓ)

CAB

Mounting	Iso-Mounted
Seat - Standard / Optional	Mechanical / Air suspension

WEIGHT

2WD w/ ROPS, lbs. (kgs)	9,061 (4 110)	9,061 (4 110)
MFD w/ ROPS, lbs. (kgs)	9,700 (4 400)	9,700 (4 400)
2WD w/ cab, lbs. (kgs)	9,766 (4 430)	9,766 (4 430)
MFD w/ cab, lbs. (kgs)	10,406 (4 720)	10,406 (4 720)

NOTE: Specifications may vary, confirm with your dealer.